

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 62074054
PUBLICATION DATE : 04-04-87

APPLICATION DATE : 27-09-85
APPLICATION NUMBER : 60214216

APPLICANT : HITACHI METALS LTD;

INVENTOR : TOKUNAGA MASAOKI;

INT.CL. : C22C 38/14 C22C 38/00 C22C 38/00 H01F 1/08

TITLE : PERMANENT MAGNET ALLOY

ABSTRACT : PURPOSE: To improve oxidation resistance and corrosion resistance by segregating elements such as Nb, Ta, V, Ti, etc., in the grain boundary of a rare earth element-Fe-B magnet alloy.

CONSTITUTION: A permanent magnet alloy has a composition represented by $R(Fe_{1-x-y}B_xM_y)A$, where R is a combination of 1 or ≥ 2 kinds among rare earth elements, M is a combination of 1 or ≥ 2 elements among Nb, Ta, V, Ti and Al, $0.02 \leq x \leq 0.3$, $0.0001 \leq y \leq 0.03$ and $4 \leq A \leq 7.5$. A powdered alloy having the above composition is compacted in the magnetic field and the resulting green compact is sintered to segregate Nb, Ta, V and Ti in the grain boundary of the alloy. In this way, oxidation resistance and corrosion resistance in the grain boundary is improved and in its turn magnetic properties, oxidation resistance, etc., of the whole permanent magnet alloy sintered compact can be improved.

COPYRIGHT: (C)1987,JPO&Japio